

X-Voice Gateway VoIP GSM/UMTS

The multi-function VoIP gateway ensuring high quality audio and easy to configure



www.x-voice.it

- Multifunction VoIP Gateway GSM/UMTS
- Availability of devices equipped with 1, 2 or 5 SIM GSM/UMTS
- High quality of audio signal
- Web interface with contextual guide
- Quick start guide and manual
- Monitoring of the audio signal quality
- 3G router, failover or backup ADSL/3G (optional)
- Support to SIP protocol
- SMS Manager (optional)
- Power consumption less than 5Wh
- Power supplier (5V-2A) and LAN cable included
- Fanless, compact size (10x8x3 cm)

X-Voice Gateway VoIP GSM/UMTS is a multi-functions IP device enabling the integration of GSM/UMTS lines in a traditional PBX IP, allowing the forwarding of the calls towards mobile phones by using one or more SIM cards (with flat fare) and reducing, in such a way, the phone costs. Once connected to the enterprise LAN, the X-Voice Gateway VoIP is easy and quick to set up thanks to its smart web wizard, a user friendly web interface enabling, among the other features, the real time monitoring of the received signal level to optimize the positioning inside the building and receiving capacity.

X-Voice Gateway VoIP GSM/UMTS is equipped with a large number of additional features (optional) such as: mobile data connection sharing (router 3G), failover or backup ADSL/3G to guarantee a continuous Internet connection in case of ADSL failure, phonebook with automatic importation of contacts, SMS Manager to send messages to one or more contacts at the same time (advertising campaigns) and to receive SMS over mail addresses or mobile phones. Needing less than 5 Wh, X-Voice Gateway allows a significant reduction of the energy cost.



www.vicosystems.it